

HEWLETT-PACKARD COMPANY
Intellectual Property Administration
P. O. Box 272400
Fort Collins, Colorado 80527-2400

PATENT APPLICATION

ATTORNEY DOCKET NO. 60990043-1

IN THE
UNITED STATES PATENT AND TRADEMARK OFFICE
RECEIVED
CENTRAL FAX CENTER

Inventor(s): ECKARD et al.

Application No.: 09/773,054

Filing Date: Jan 31, 2001

Title: SPECIAL SERVICE STATION MODULE FOR EXTRA SERVICING

Confirmation No.: 6040

Examiner: NGHIEM, M.

Group Art Unit: 2863

Mail Stop
Commissioner For Patents
PO Box 1450
Alexandria, VA 22313-1450

TRANSMITTAL LETTER FOR RESPONSE/AMENDMENT

Sir:

Transmitted herewith is/are the following in the above-identified application:

- () Response/Amendment
() New fee as calculated below
() No additional fee
(X) Other: Transmittal of Revised App.Br./Rev. App.Br. (fee \$ _____)
- () Petition to extend time to respond
() Supplemental Declaration

CLAIMS AS AMENDED BY OTHER THAN A SMALL ENTITY						
(1) FOR	(2) CLAIMS REMAINING AFTER AMENDMENT	(3) NUMBER EXTRA	(4) HIGHEST NUMBER PREVIOUSLY PAID FOR	(5) PRESENT EXTRA	(6) RATE	(7) ADDITIONAL FEES
TOTAL CLAIMS		MINUS		= 0	X \$50	\$ 0
INDEP. CLAIMS		MINUS		= 0	X \$200	\$ 0
I] FIRST PRESENTATION OF A MULTIPLE DEPENDENT CLAIM					+ \$360	\$ 0
EXTENSION FEE	1ST MONTH \$120.00	2ND MONTH \$450.00	3RD MONTH \$1020.00	4TH MONTH \$1590.00		\$ 0
OTHER FEES						\$
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT						\$ 0

Charge \$ 0 to Deposit Account 08-2025. At any time during the pendency of this application, please charge any fees required or credit any overpayment to Deposit Account 08-2025 pursuant to 37 CFR 1.25. Additionally please charge any fees to Deposit Account 08-2025 under 37 CFR 1.16, 1.17, 1.19, 1.20 and 1.21. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

(X) I hereby certify that this paper is being transmitted to the Patent and Trademark Office facsimile number (571) 273-8300 on Aug 18, 2005
Number of pages: 31

Typed Name: Larry K. Roberts

Signature: 

ECKARD et al.

By 

Larry K. Roberts

Attorney/Agent for Applicant(s)
Reg. No. 28,464

Date: Aug 18, 2005

Telephone No.: (949) 640-6200

RECEIVED
CENTRAL FAX CENTER

AUG 18 2005

PATENT
60990043-1

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

In re Application of:

Eckerd et al.

Serial No. 09/773,054

Filed: 01/31/2001

For: SPECIAL SERVICE STATION
MODULE FOR EXTRA SERVICING

) Art Unit: 2863

) Examiner: Nghiem, M.

TRANSMITTAL OF REVISED APPEAL BRIEF

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

In a office action mailed August 5, 2005, pursuant to the Board's "Order Returning Undocketed Appeal to Examiner" mailed May 31, 2005, a requirement was set out to submit a complete new brief to comply with 37 CFR 41.37(c)(1)(ix) (Evidence Appendix) and 37 CFR 41.37(c)(1)(x) (Related Case Appendix). Submitted herewith is a complete new brief, entitled Revised Appeal Brief. This revised brief differs from the brief filed December 9, 2004 in that it includes pages 23-24 entitled, respectively "Evidence Appendix" and "Related Proceedings Appendix."


09/773,054

2

60990043-1

Appellant respectfully submits that the revised brief complies with 37 CFR 41.37(c)(1)(ix) and 37 CFR 41.37(c)(1)(x), and respectfully requests that the revised brief be entered, and the case returned to the Board for action on the appeal.

Respectfully submitted,



Larry K. Roberts
Registration No. 28,464

Dated: 8-18-2005

Law Offices of Larry K. Roberts, Inc.
P.O. Box 8569
Newport Beach, CA 92658-8569
Telephone (949) 640-6200
Facsimile (949) 640-1206

08/18/05 09:45 FAX 949 640 1206

LARRY K. ROBERTS, INC → PTO

004

RECEIVED
CENTRAL FAX CENTER

PATENT
60990043-1

AUG 18 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

In re Application of:

ECKARD et al.

Serial No. 09/773,054

Filed: 01/31/2001

For: SPECIAL SERVICE STATION
MODULE FOR EXTRA SERVICING

Art Unit: 2863

Examiner: Nghiem, M.

REVISED APPEAL BRIEF

TABLE OF CONTENTS

I.	REAL PARTY IN INTEREST	1
II.	RELATED APPEALS AND INTERFERENCES	1
III.	STATUS OF ALL THE CLAIMS	1
IV.	STATUS OF ALL AMENDMENTS FILED SUBSEQUENT TO REJECTION	2
V.	SUMMARY OF THE INVENTION	2
VI.	GROUND OF REJECTION TO BE REVIEWED ON APPEAL ...	5
VII.	ARGUMENT	5
	A. The Requirements for Anticipation under Section 102(e)	5
	B. The Rejection Under Section 102(e) Should Be Reversed	10
	C. The Requirements of 35 USC §103	11
	D. A Prima Facie Case of Obviousness Has Not Been Established...	13
VII.	SUMMARY	14
	APPENDIX I	24
	EVIDENCE APPENDIX	25
	RELATED PROCEEDINGS APPENDIX	25

TABLE OF AUTHORITIES

35 USC § 102(e)	5
35 USC § 103(a)	5
MPEP 2131	5
<u>In re Wright</u> , 6 USPQ 2d 1959, 1961 (Fed.Cir. 1988)	10
<u>In re Sernaker</u> , 702 F.2d 989 (Fed.Cir. 1983).	10
<u>In re Sernaker</u> , <u>supra</u> , at 995-996	10
<u>In re Shuman</u> , 361 F.2d 1008 (CCPA 1966)	10
<u>In re Fritch</u> , 23 USPQ 1780, 1783 (Fed.Cir. 1992)	11
35 USC § 102	13
35 USC § 103	10, 13

RECEIVED
CENTRAL FAX CENTER

PATENT
60990043-1

AUG 18 2005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

In re Application of:

Eckerd et al.

Serial No. 09/773,054

Filed: 01/31/2001

For: SPECIAL SERVICE STATION
MODULE FOR EXTRA SERVICING

Art Unit: 2863

Examiner: Nghiem, M.

REVISED APPEAL BRIEF

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This appeal is taken from the Office's rejection of Claims 9, 12, 21, 25 and 34-44 mailed July 1, 2004, in the subject application.

I. REAL PARTY IN INTEREST.

The real party in interest is the assignee, Hewlett-Packard Development Company, L.P.

II. RELATED APPEALS AND INTERFERENCES.

There are no related appeals, interferences or judicial proceedings known to appellants, the appellants' legal representative, or assignee.

III. STATUS OF ALL THE CLAIMS.

Claims 1-30 were filed with this application. During the course of prosecution before the Primary Examiner, Claims 31-46 were added, Claims 1-4, 10-11, 13, 17-18, 23-24, 26, 28-28 were cancelled. Claims 5-9, 12, 14-16, 19-22, 25, 27 and 30-46 in their present form appear in Appendix 1.

09/773,054

2

60990043-1

Claims 5-8, 14-16, 19, 20, 22, 27, 30-33, 45 and 46 have been allowed.
Claims 9, 12, 21, 25 and 34-44 are at issue in this appeal.

IV. STATUS OF ALL AMENDMENTS FILED SUBSEQUENT TO REJECTION.

No amendments have been filed subsequent to the rejection mailed July 1, 2004, which is the subject of this appeal.

It is noted that, while the rejection mailed July 1, 2004, was not a final rejection, the subject matter of all appealed claims has been twice rejected.

V. SUMMARY OF THE INVENTION.

The page and line numbers referred to herein are to the specification; reference characters are found in the drawing.

Claim 9 is drawn to a method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module [230; FIGS. 4A-4B] removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module [230A-230E; FIGS. 6-10] with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module [9:25 - 10:18].

Claim 12 is drawn to a method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module [230; FIGS. 4A-4B] removably installed on the printer, comprising:

09/773,054

3

60990043-1

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module [230C; FIG. 8] with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module, wherein said printhead-related service condition includes ink accumulation on the nozzle plate, and wherein the second service module includes a wiper fabricated of silicon, or a textile, or a special rubber for removing the ink accumulation [9:25 - 10:18; 13:31 - 14:4].

Claim 21 is drawn to a method for servicing an inkjet printer including an inkjet printhead and a removable first service module [230; FIGS. 4A-4B], comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module [230A-230E; FIGS. 6-10] with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module [9:25 - 10:18].

Claim 25 is drawn to a method for servicing an inkjet printer including an inkjet printhead and a removable first service module [230; FIGS. 4A-4B], comprising:

providing a second service module [230C; FIG. 8] different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module

09/773,054

4

60990043-1

being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

installing the second service module in the printer;

conducting a printhead-related service operation using the second service module;

wherein said printhead-related service condition includes ink accumulation on a printhead nozzle plate, and wherein the second service module includes a wiper fabricated of silicon, or a textile, or a special rubber for removing the ink accumulation [9:25 - 10:18; 13:31 - 14:4].

Claim 34 is drawn to a method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer [230; FIGS. 4A-4B], comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module [230A-230E; FIGS. 6-10] with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module [9:25 - 10:18].

Claim 40 is drawn to a method for servicing an inkjet printer including an inkjet printhead and a removable first service module [230; FIGS. 4A-4B], comprising:

providing a second service module [230A-230E; FIGS. 6-10] different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module; and

installing the second service module in the printer;

conducting a printhead-related service operation using the second service module [9:25 - 10:18].

09/773,054

5

60990043-1

VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL.

The grounds of rejection to be reviewed on appeal are:

- (i) whether Claims 9, 21 and 34-44 are anticipated under 35 USC 102(e) by Garcia et al. ("Garcia") (US 6,042,216); and
- (ii) whether Claims 12 and 25 are unpatentable under 35 USC 103(a) over Garcia in view of Wojcik (US 6,250,736).

VII. ARGUMENT.

For purposes of this appeal, appellants are content to stand on the differences between the claimed invention and the applied references discussed below, because these differences are sufficient to establish that a prima facie case of anticipation and obviousness has not been established, and the applied references do not describe, teach or suggest appellants' invention. Appellants do not concede, however, that other differences do not exist.

A. The Requirements for Anticipation under Section 102.

A claim is anticipated only if each and every element as set forth in the claim is found, either expressly or inherently described, in a single prior art reference. The identical invention must be shown in as complete detail as contained in the claim. The elements must be arranged as required by the claim. MPEP 2131.

For reasons discussed below, the rejection under Section 102 should be reversed.

B. The Rejection under Section 102(e) Should Be Reversed.

Claims 9, 21 and 34-44 stand rejected as being anticipated by Garcia et al. ("Garcia"), U.S. 6,042,216. This rejection is should be reversed, since a prima facie case of anticipation has not been established, and the reference does not describe each element of Claims 9 and 21.

The rejection does not address all features of the rejected claims, and thus fails to establish a prima facie case of anticipation.

09/773,054

6

60990043-1

Garcia describes an ink delivery system including a printhead and a service station module. The module is dedicated solely to a single printhead and can be removed and replaced at the same time the printhead is removed. See, e.g. Garcia at 8:61 to 9:7.

Appellants respectfully disagree with the Examiner's recitation of the teachings of Garcia. With respect to Claims 9, 21, 34, 36, 40 and 41:

1. The Examiner reads wiper 234 or capper 236 as corresponding to a first service module.

2. The Examiner asserts that Garcia discloses "identifying a printhead-related service condition (Abstract, lines 3-6) not adequately addressed by servicing the printer with the first service module being in an un-worn condition (complete servicing includes other service module such as a capper, a spittoon and a primer connection. Abstract, lines 6-8)." Thus, the "other service module" is interpreted by the Examiner as another component on the same service station module as the wiper 234 or capper 236.

3. The Examiner further asserts that Garcia discloses "providing a second service module (capper 236 or wiper 234) with a service function different from the first service module (Fig. 14a) and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module (Fig. 23)." Appellants respectfully disagree with this interpretation of Garcia. FIG. 23 is an exploded isometric view of the service station module of FIGS. 14A-14B; there is no teaching or description that a wiper 234 is removably installable with respect to a capper 236. Just because the elements of the service module of FIGS. 14A-14B are shown in an exploded view to show details of the service module in a patent application does not support the Examiner's assertion that elements 234 or 236 are intended to be removably installable with respect to the service module or the other elements.

4. The Examiner alleges that Garcia describes that "the capper (236) is removable with respect to the wiper (234) by removing a screw (see Fig. 14a)." Appellants respectfully deny that Garcia provides this teaching.

09/773,054

7

60990043-1

The allegation amounts to speculation that Fig. 14a illustrates removing a screw to remove the capper. Yet there is no screw specifically illustrated, nor is there any written description supporting the speculation. Instead, Garcia describes that the service module 230 shown in FIG. 14a is "removed and replaced at the same time that the associated printhead is removed" (8:61 to 9:7). No description appears to support the Examiner's speculation that the capper is intended to be replaced separately with respect to the wiper.

5. The Examiner further asserts Garcia discloses "providing the second service module to the printer user (234, 236 is available for use, Fig. 23), wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module (column 6, line 61 - column 7, line 7, column 8 line 7-18) provide human-readable instructions on how to use the second service module 234, 236)." These assertions do not meet the claim limitations. There is no showing that the alleged instructions are provided to the printer user, i.e. that the Garcia document is provided to the printer user. The Examiner provides a discussion of the disclosure of an invention in a US Patent (including Garcia), as being intended for one of ordinary skill in the art to make use of the invention, as well as requirements of Section 112, but does not address how the Garcia reference teaches that the Garcia patent is provided to the printer user. Nor is there any showing as to how the requirements of Section 112, pertaining to the claimed invention of Garcia, are relevant here.

6. Moreover, there is no description of how the user can or should use a "module" 234 or 236 as the Examiner interprets Garcia. The discussion in Garcia is of replacement of the service module 230, not of 234 or 236 with respect to 236 or 234.

Appellants respectfully submit that Garcia does not describe at least the following limitations of Claims 9, 21, 34 and 40:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition

09/773,054

8

60990043-1

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module

(Claim 9)

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module

(Claim 21)

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module

(Claim 34)

providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn

09/773,054

9

60990043-1

condition, the second service module removably installable on the printer and with respect to the first service module; and
installing the second service module in the printer;
conducting a printhead-related service operation using the second service module.

(Claim 40)

The claims depending from Claims 34 and 40 are also not anticipated by Garcia, for the reasons discussed above regarding the independent claims. Moreover, Garcia does not describe the following exemplary limitations:

removing the first service module from the printer;
installing the second service module in the printer;
using the set of instructions and the second service module, conducting a special servicing operation. (Claim 37)

The Examiner asserts that Garcia describes these limitations of Claim 37, stating that Garcia describes "removing the first service module from the printer (by removing service module, column 8, lines 65-67), installing the second service module in the printer (by replacing with new service module, column 8, line 67), and using the set of instructions and the second service module, conducting a special servicing operation (column 8, lines 63-64)." (Rejection at page 4). These allegations do not meet the claim limitations. While Garcia describes replacing the service module with a new service module when the printhead is replaced, Garcia does not describe that the new service module is "different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition" as recited in Claim 34, from which Claim 37 depends.

Similar considerations apply to dependent Claims 38 and 42, which recite that "wherein the second service module includes a brush to remove the fibers." The Examiner asserts that the second service station includes a brush (wiper 234) to remove the fibers. However, this assertion does not meet that claim limitation of the corresponding independent claim, i.e. that the second

09/773,054

10

60990043-1

service module is "different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition."

The same reasoning applies to Claims 39, 43 and 44. The Examiner's assertions are that the replacement service module has the features recited in these dependent claims, but does not address the limitations of the corresponding independent claim i.e. that the second service module is "different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition."

Because Garcia does not describe each element of the rejected claims, the rejection under Section 102 should be reversed.

C. The Requirements of 35 USC §103.

35 USC §103 requires that the invention as a whole must be considered in obviousness determinations. The invention as a whole embraces the structure, its properties and the problem it solves. In re Wright, 6 USPQ2d 1959, 1961 (Fed.Cir. 1988).

In order to provide a basis for obviousness, the applied references must be related to the subject matter of the invention in issue and must suggest (expressly or by implication) the combination of the invention in issue. In re Sernaker, 702 F.2d 989 (Fed.Cir. 1983).

Further, the combined teachings of the prior art references should suggest the advantage of combining the teachings. In re Sernaker, supra, at 995-996.

In determining the combined teachings of the applied references, the subject matter of the claimed invention must not be utilized to provide hindsight reconstruction of the applied references. As stated by the Court of Customs and Patent Appeals In re Shuman, 361 F.2d 1008 (CCPA 1966):

It is impermissible to first ascertain factually what appellant did and then view the prior art in such a manner as to select from the random facts of that art only those which may be modified and

09/773,054

11

60990043-1

then utilized to reconstruct appellants' invention from such prior art. 361 F.2d at 1012.

The Examiner bears the burden of establishing a prima facie case of obviousness based on the prior art. "... This burden can be satisfied only by showing some objective teaching in the prior art or that knowledge generally available to one of ordinary skill in the art would lead that individual to combine the relevant teachings of the references.' The patent applicant may then attack the Examiner's prima facie determination as improperly made out, or the applicant may present objective evidence tending to support a conclusion of nonobviousness." In re Fritch, 23 USPQ 1780, 1783 (Fed.Cir. 1992).

Appellants submit that the Primary Examiner has not established prima facie that the claimed invention would have been obvious in view of the applied references, and that the references do not teach or suggest the claimed invention.

D. A Prima Facie Case of Obviousness Has Not Been Established.

Claims 12 and 25 stand rejected as being unpatentable over Garcia in view of Wojcik (U.S. 6,250,736). This rejection is respectfully traversed on the grounds that a prima facie case of obviousness has not been established, and the references do not teach or suggest the invention of these claims.

Claim 12 is drawn to a method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

- identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

- providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module, wherein said printhead-related service condition includes ink accumulation on the nozzle plate, and wherein the second service module includes a wiper fabricated of silicon, or a textile, or a special rubber for removing the ink accumulation.

09/773,054

12

60990043-1

Garcia has been addressed above, and does not address the problem of a printhead-related service condition not adequately addressed by servicing the first service module being in an un-worn condition. Garcia teaches replacing the service with a fresh service module at the same time that the associated printhead is removed. 8:61 to 9:4. Moreover, there is no teaching of providing a second service module with a service function different from the first service module that is removably installable on the printer and with respect to the first service module.

Wojcik is cited only for its disclosure of a wiper of silicon or rubber, and does not supply any missing teachings discussed above regarding Garcia.

The references fail to teach or suggest all claim limitations of Claim 12. The rejection should be withdrawn.

Similar considerations apply to Claim 25, drawn to a method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:

- providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

- installing the second service module in the printer;

- conducting a printhead-related service operation using the second service module;

- wherein said printhead-related service condition includes ink accumulation on a printhead nozzle plate, and wherein the second service module includes a wiper fabricated of silicon, or a textile, or a special rubber for removing the ink accumulation.

Because the applied references do not teach or suggest all claim limitations, the rejection of Claim 25 should be withdrawn.

09/773,054


13

60990043-1

VII. SUMMARY

The rejections under 35 USC §§ 102 and 103 must be reversed. A prima facie case of anticipation and of obviousness has not been made, and the cited references do not teach or suggest the claimed invention.

Respectfully submitted,



Larry K. Roberts
Registration No. 28,464

Dated: 8-18-2005

Law Offices of Larry K. Roberts, Inc.
P.O. Box 8569
Newport Beach, CA 92658-8569
Telephone (949) 640-6200
Facsimile (949) 640-1206

09/773,054

14

60990043-1

APPENDIX I

Claims 1-4 (Canceled)

5. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module;

removing the first service module from the printer;

installing the second service module in the printer in place of the first service module;

using the second service module, conducting a special printhead-related servicing operation.

6. (Original) The method of claim 5, further comprising:

after completion of the special printhead-related servicing operation, removing the second service module from the printer; and

install the first service module in the printer in place of the second service module.

7. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service

09/773,054

15

60990043-1

condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of machine readable printer instruction code for loading into the printer.

8. (Original) The method of claim 7 wherein the printer is controlled by a host computer, and wherein the step of using the set of instructions includes downloading the set of printer instruction code from the host computer.

9. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module.

Claims 10-11 (Canceled)

12. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

09/773,054

16

60990043-1

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module, wherein said printhead-related service condition includes ink accumulation on the nozzle plate, and wherein the second service module includes a wiper fabricated of silicon, or a textile, or a special rubber for removing the ink accumulation.

Claims 13 (Canceled)

14. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module, wherein said printhead-related service condition includes ink on a printhead carriage interconnect, and the second service module includes a brush arranged to clean the interconnect.

15. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module, wherein said printhead-related service condition includes vibration or shock incurred during shipment or moving of the printer, and the second service module includes a special capping structure

09/773,054

17

60990043-1

having a range of movement along an axis generally transverse to a nozzle array of the printhead, and a bias structure which urges the capping structure toward and into engagement with the printhead during a capping procedure.

16. (Original) The method of claim 15 wherein the special capping structure includes a relative hard, non-resilient cap structure which contacts the printhead during the capping procedure.

Claims 17-18 (Canceled)

19. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:
providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of machine readable printer instruction code for loading into the printer;

installing the second service module in the printer;

conducting a printhead-related service operation using the second service module.

20. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:

providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the printer is controlled by a host

09/773,054

18

60990043-1

computer, and the step of providing a set of instructions includes downloading the set of printer instruction code from the host computer;
installing the second service module in the printer;
conducting a printhead-related service operation using the second service module.

21. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:
identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module;

providing a set of instructions for using the second service module with the inkjet printer to the printer user, wherein the step of providing a set of instructions includes providing a set of human-readable instructions for using the second service module.

22. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:

providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

installing the second service module in the printer;

conducting a printhead-related service operation using the second service module;

after completion of the printhead-related servicing operation, removing the second service module from the printer; and

installing the first service module in the printer in place of the second service module.

09/773,054

19

60990043-1

Claims 23-24 (Canceled)

25. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:
providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

installing the second service module in the printer;

conducting a printhead-related service operation using the second service module;

wherein said printhead-related service condition includes ink accumulation on a printhead nozzle plate, and wherein the second service module includes a wiper fabricated of silicon, or a textile, or a special rubber for removing the ink accumulation.

Claims 26 (Canceled)

27. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead and a removable first service module, comprising:
providing a second service module different from the first service module and adapted to address a printhead-related service condition not adequately addressed by the first service module being in an un-worn condition, the second service module removably installable on the printer and with respect to the first service module;

installing the second service module in the printer;

conducting a printhead-related service operation using the second service module;

wherein said printhead-related service condition includes ink on a printhead carriage interconnect, and the second service module includes a cleaning element arranged to clean the interconnect during a special cleaning mode with the printhead removed from the carriage.

Claims 28-29 (Canceled)

09/773,054

20

60990043-1

30. (Previously presented) A special service module for use in an inkjet printing system including an inkjet printhead and a standard service module removably installed in the printing system, the special service module configured to be removably installed in the printing system in place of the standard service module to perform a special service function on the printhead which is not performed by the standard service module being in an un-worn condition, the special service module removably installable on the printer and with respect to the standard service module.

31. (Previously presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition;

removing the first service module from the printer;

installing the second service module in the printer in place of the first service module;

using the second service module, conducting a special printhead-related servicing operation;

after completion of the special printhead-related servicing operation, removing the second service module from the printer; and

installing the first service module in the printer in place of the second service module.

32. (Previously presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module in an un-used condition, said printhead-related service condition including vibration or shock incurred during shipment or moving of the printer, the second service module including a special capping structure having a range of movement along an axis generally

09/773,054

21

60990043-1

transverse to a nozzle array of the printhead, and a bias structure which urges the capping structure toward and into engagement with the printhead during a capping procedure, and wherein the special capping structure including a relative hard, non-resilient cap structure which contacts the printhead during the capping procedure;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition; and

performing the capping procedure with the second service module installed in the printer, and maintaining contact between the non-resilient cap structure and the printhead to prevent a pumping action on the printhead when subjected to vibration and shock.

33. (Previously presented) The method of claim 32, wherein a constant closed volume is maintained between the cap structure and the printhead during the capping procedure.

34. (Previously Presented) A method for servicing an inkjet printer including an inkjet printhead with a nozzle plate and a first service module removably installed on the printer, comprising:

identifying a printhead-related service condition not adequately addressed by servicing the printer with the first service module being in an un-worn condition;

providing a second service module with a service function different from the first service module and adapted to address said printhead-related service condition, the second service module removably installable on the printer and with respect to the first service module.

35. (Previously Presented) The method of claim 34, further including: providing the second service module to the printer user.

36. (Previously Presented) The method of claim 35, further comprising providing a set of instructions for using the second service module with the inkjet printer to the printer user.

09/773,054

22

60990043-1

37. (Previously Presented) The method of claim 36, further comprising:
removing the first service module from the printer;
installing the second service module in the printer;
using the set of instructions and the second service module, conducting
a special servicing operation.

38. (Previously Presented) The method of claim 34, wherein said
printhead-related service condition comprises fibers accumulating on the
printhead nozzle plate, and wherein the second service module includes a brush
to remove the fibers.

39. (Previously Presented) The method of claim 34, wherein said
printhead-related service condition includes ink accumulation on the nozzle
plate, and wherein the second service module includes a wiper or applicator
having applied thereto a cleaning fluid for removing the ink accumulation.

40. (Previously Presented) A method for servicing an inkjet printer
including an inkjet printhead and a removable first service module, comprising:
providing a second service module different from the first service module
and adapted to address a printhead-related service condition not adequately
addressed by the first service module being in an un-worn condition, the second
service module removably installable on the printer and with respect to the first
service module; and

installing the second service module in the printer;
conducting a printhead-related service operation using the second service
module.

41. (Previously Presented) The method of Claim 40, further comprising
providing a set of instructions for using the second service module with the inkjet
printer to the printer user.

42. (Previously Presented) The method of claim 40, wherein said
printhead-related service condition comprises fibers accumulating on a printhead
nozzle plate, and wherein the second service module includes a brush to remove
the fibers.

09/773,054

23

60990043-1

43. (Previously Presented) The method of claim 40, wherein said printhead-related service condition includes ink accumulation on the nozzle plate, and wherein the second service module includes a wiper or applicator having applied thereto a cleaning fluid for removing the ink accumulation.

44. (Previously Presented) The method of claim 40, wherein said printhead-related service condition includes global depriming of the printhead or ink starvation of the printhead, and wherein the second service module includes a negative pressure primer.

45. (Previously Presented) An inkjet printing system, comprising:
an inkjet printhead;
a service area for performing service functions on the printhead;
a first service module for removable mounting at the service area to perform service functions on the printhead during a standard printhead service mode;
a second service module for removable mounting at the service area in place of the first service module to perform a different service function from that performed by the first service module in an unused condition on the printhead during a special printhead service mode.

46. (Previously Presented) The system of Claim 45 further comprising:
a printhead carriage for mounting the printhead and arranged for traversing movement along a print area and for moving to the service area;
a service carriage for removably mounting the first service module or the second service module.

09/773,054

24

60990043-1

EVIDENCE APPENDIX

No evidence submitted pursuant to 37 CFR Sections 1.130, 1.131 or 1.132, or any other evidence entered by the Examiner, is relied upon by appellant in this appeal.

08/18/05 09:50 FAX 949 640 1206

LARRY K. ROBERTS, INC → PTO

031

09/773,054

25

60990043-1

RELATED PROCEEDINGS APPENDIX

There are no related proceedings and thus no decisions rendered in any such proceeding.